Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the subject application.

Listing of Claims:

What is claimed is:

- 1. (Currently Amended) A process of providing corrosion protection for a metal by coating said metal with a thiol compound, comprising:
- a. dissolving or dispersing said thiol compound in a solvent and preparing a solution or dispersion including 20 to 50 mM of the thiol compound,
 - b, treating said metal with said solution or dispersion in the range of 3 to 11 seconds,
- c. drying or curing the treated metal, wherein a coating consisting essentially of said thiol
 compound is formed directly on the metal surface, and

thereby increasing the corrosion resistance of said metal without using chrome, and wherein said metal is selected from the group consisting of hot rolled steel sheet, cold-rolled steel sheet, hot-dipped metallic coated steel sheets, electroplated metallic coated steel sheets, aluminum sheets, aluminum alloy sheets, zinc sheets, and zinc alloy sheets.

- 2. (Previously Presented) A process according to Claim 1 wherein said thiol compound has the general formula, R(CH₂)_nSH, where R is selected from the group consisting of methyl, carboxyl, hydroxyl, formyl, and amide, and n is in the range of 7 to 21.
- (Previously Presented) A process according to Claim 1 wherein said thiol compound is 1octadecanethiol.
- 4. (Cancelled)

Page 3 Serial Number: 10/786,379 Docket:YOU102 Filing Date: February 25, 2004

Title: Method of Protecting Metals From Corrosion Using Thiol Compounds

(Previously Presented) A process according to Claim 1 wherein said metal includes coatings of one or more layers selected from the group consisting of lead, lead alloy, nickel,

nickel alloy, zinc, zinc layer, tin, and tin alloy.

6. (Cancelled)

AMENDMENT

A process according to Claim 1 wherein said solvent is selected 7. (Previously Presented)

from the group consisting of alcohols, glycols, acetone, toluene, ethyl acetate, hexane, furan,

tetrahydrofuran (THF), methylene chloride, ethers, formic acid, formamide, N,N-dimethyl formamide, acetonitrile, alkanes, turpentine, benzene, butyl acetate, petroleum ester, xylene,

carbon tetrachloride, mineral spirits, and water; and combinations thereof,

8. (Previously Presented) A process according to Claim 7 wherein said solvent is selected

from the group consisting of ethanol, 1-propanol, 1-butanol, and mixtures thereof.

9. (Cancelled)

10. (Previously Presented) A process according to Claim 1 wherein said metal substrate is

coated with said solution or dispersion by using a means selected from the group consisting of

immersion, spray, painting, roll coating, and flow coating.

11. (Previously Presented) A process according to Claim 1, wherein said metal is coated with

said solution or dispersion by immersion.

12. (Cancelled)

13. (Currently Amended) A process of providing corrosion protection for a galvanized steel

by coating said steel with a thiol compound, comprising:

Title: Method of Protecting Metals From Corrosion Using Thiol Compounds

- a. dissolving or dispersing said thiol compound in a solvent and preparing a solution or dispersion including 20 to 50 mM of the thiol compound,
- b. treating said galvanized steel with said solution or dispersion in the range of 3 to 11 seconds.
- c. drying or curing the treated galvanized steel, wherein a coating consisting essentially of said thiol compound is formed directly on said galvanized steel and

thereby increasing the corrosion resistance of said galvanized steel without using chrome,

- 14. (Original) A process according to Claim 13 wherein said galvanized steel is electrogalvanized.15. (Cancelled)
- 16. (Cancelled)17. (Cancelled)
- 18. (Cancelled)
- 19. (Cancelled)
- 20. (Cancelled)
- 21. (Cancelled)
- 22. (Cancelled)
- 23. (Cancelled)